



AFD Mound Gauge

This tool allows a mound to be built from scratch as well to check for proper slope. The Powder Coated gauge is made of 1 1/2" metal square tubing with calibrated drop down bars every 1' to indicate the proper slope for a regulation pitchers mound. The pivot point is 18" in front of the rubber and 1" below grade of the rubber. The front portion of the gauge can be set by a skid or a wheel. Gauge also has an attached level with an adjustable leg to set for the proper slope. The drop down bars indicates when to fill or to cut by scarring the clay. Using a Hula Hoe or rake to cut down the high spots. The AFD Mound Gauge will rotate at a 180° angle allowing for that consistent grade to the base of the mound. Gauge disassembles for easy transportation and storage.



\$395 plus shipping
(503) 698-6383
(503) 698-7289 Fax
hebrard@athleticfield.com
www.athleticfield.com



"When the Game is on the Line,
Call Athletic Field Design"



- Training
- Consulting
- Field layout
- Laser grading
- Logo painting
- Infield renovation
- New infield installation
- Synthetic Field Maintenance
- Tournament & Playoff Prep
- Aeration, Topdressing, Slice

ATHLETIC FIELD DESIGN
AFD
Portland, OR
ATHLETIC FIELD DESIGN
(503) 698-6383
hebrard@athleticfield.com
www.athleticfield.com
12586 SE Bluff Drive
Clackamas, OR 97015